

NitriTech®



767PF SERIES

- Nitrile Examination Glove
- 4 mil 1.5 AQL • Class 1 Medical Device
- 100% Nitrile Polymer
- 9.5 Inch Length • Single Use
- Powder Free • Blue Color
- Beaded Cuff • Ambidextrous
- Manufactured to internationally recognized ISO 9001 and EN46001 Quality Systems
- FDA 510 LISTING RE: K964148
- Complies with current revision of ASTM D6319
- CE Approved

Main Components:

Nitrile Polymer, Sulphur, Zinc Oxide, Zinc Dibutylthiocarbamate, Titanium Dioxide and Blue Pigment (C.I. Number: 74160).

Available in Sizes: Small, Medium, Large, X-Large, 2X-Large, 3X-Large



Packaged 100 gloves per dispenser box, 10 dispenser boxes per case.

Instruction for Use and Storage:

1. Choose the appropriate glove size to avoid hand fatigue
2. It is recommended to visually check the glove condition intermittently during use. Discontinue using if serious physical (swelling) changes occur.

NOTE: Glove performance quoted based on laboratory data and may vary depending on the actual condition of use. The user should follow the instructions above during application.

3. Do not use the glove in contact with hazardous chemicals or solvents for long durations.
4. Storage: Keep ideally at 15C to 30C and 40% to 65% room humidity.
5. With proper storage, projected 5 year expiration date.

Glove is made only using listed materials and levels as outlined in the Code of Federal Regulations (21CFR), parts 170-199, and is acceptable for use in food, medical and pharmaceutical applications.



For more information please contact us at:
www.summitglove.com

EMAIL: summit@summitglove.com
310 S. Grant St. • P.O. BOX 328 • Minerva, OH 44657-0328
• Phone (330) 868-0066 • Fax (330) 868-4169
• Toll Free (800) 245-7117



DIMENSIONS

SIZES	LENGTH MILLIMETERS/MIN.	WIDTH MILLIMETERS/MIN.	CUFF PALM FINGER		
			THICKNESS/MILS (DOUBLE LAYER) +/- 1.0 mil		
SMALL	240mm	83 +/-4	6.4	8.0	12.0
MEDIUM	240mm	89 +/-4	6.4	8.0	12.0
LARGE	240mm	104 +/-4	6.4	8.0	12.0
X-LARGE	240mm	114 +/-4	6.4	8.0	12.0
XX-LARGE	240mm	118 +/-4	6.4	8.0	12.0
XXX-LARGE	240mm	124 +/-4	6.4	8.0	12.0

PHYSICAL PROPERTIES BEFORE AGING

TENSILE STRENGTH	ULTIMATE ELONGATION
14.0 MPa	500%

WEIGHT AND TOLERANCE

SIZES	WEIGHT
SMALL	4.3 +/- 0.3 gram
MEDIUM	5.0 +/- 0.3 gram
LARGE	5.7 +/- 0.3 gram
X-LARGE	6.3 +/- 0.3 gram
XX-LARGE	7.0 +/- 0.3 gram
XXX-LARGE	7.2 +/- 0.3 gram

CHEMICAL PROPERTIES

Oil and Solvent Swelling	Specification
1) Palm Oil (%)	max. 3.0
2) Heptane (%)	max. 15.0
3) Toluene (%)	max. 300
4) Tetrachloroethylene (%)	max. 200